


CAMERA

## TD-9540S4L-C

4MP Dual Illumination Water-proof  
Turret Network Camera



- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution: 4MP ( 2560 × 1440)
- Auto day/night switch
- 3D DNR, WDR, HLC, BLC, etc.
- ROI coding
- Support smart supplement light
- 10~20m white light view distance; 20~30m IR view distance
- DC12V/PoE power supply
- IP 67 ingress protection
- Support dual streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support line crossing detection & region intrusion detection
- Support SMD



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23<sup>rd</sup> Floor, Block B4, Building NO.9, Shenzhen Bay  
Eco-Technology Park, Nanshan District, Shenzhen, Guangdong  
Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777


E-mail: [overseas@tvt.net.cn](mailto:overseas@tvt.net.cn)

## SPECIFICATIONS

| Model                      | TD-9540S4L-C                                                                                                                                                               |            |           |          |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------|----------|
| Specifications             |                                                                                                                                                                            |            |           |          |
| Camera                     |                                                                                                                                                                            |            |           |          |
| Image Sensor               | 1 / 3 "CMOS                                                                                                                                                                |            |           |          |
| Image Size                 | 2560×1440                                                                                                                                                                  |            |           |          |
| Electronic Shutter         | 1 / 3s ~ 1 / 100000s                                                                                                                                                       |            |           |          |
| Iris Type                  | Fixed Iris                                                                                                                                                                 |            |           |          |
| Min. Illumination          | 0.09 lux @F2.2, AGC ON; 0 lux (Illuminator on)                                                                                                                             |            |           |          |
| Lens                       | 2.8mm@F2.2, Horizontal FoV: 96°;Vertical FoV:53.7°;Diagonal FoV:112°<br>3.6mm@F2.2, Horizontal FoV:74.5°;Vertical FoV:41.5°;Diagonal FoV:86.5°                             |            |           |          |
| Focus                      | Fixed                                                                                                                                                                      |            |           |          |
| Lens Mount                 | M12                                                                                                                                                                        |            |           |          |
| Day&Night                  | ICR                                                                                                                                                                        |            |           |          |
| Wide Dynamic Range         | Digital WDR                                                                                                                                                                |            |           |          |
| BLC                        | Yes                                                                                                                                                                        |            |           |          |
| HLC                        | Yes                                                                                                                                                                        |            |           |          |
| Digital NR                 | Yes                                                                                                                                                                        |            |           |          |
| S/N Ratio                  | ≥ 50dB                                                                                                                                                                     |            |           |          |
| Angle Adjustment           | Pan: 0°~360°; Tilt:0°~75°;Rotation: 0°~360°                                                                                                                                |            |           |          |
| DORI Distance              |                                                                                                                                                                            |            |           |          |
| Lens                       | Detect                                                                                                                                                                     | Observe    | Recognize | Identify |
| 2.8mm                      | 57m(187ft)                                                                                                                                                                 | 23m(75ft)  | 11m(36ft) | 6m(20ft) |
| 3.6mm                      | 76m(249ft)                                                                                                                                                                 | 31m(102ft) | 15m(49ft) | 8m(26ft) |
| Image                      |                                                                                                                                                                            |            |           |          |
| Video Compression          | Main stream: H.265+ / H.265 / H.264 + / H.264<br>Sub stream: H.265+ / H.265 / H.264 + / H.264 / MJPEG                                                                      |            |           |          |
| H.265 Compression Standard | Main Profile@Leve4.1 High Tier                                                                                                                                             |            |           |          |
| Resolution                 | 4MP ( 2560 × 1440 ), 3MP ( 2304 × 1296 ), 1080P ( 1920 × 1080 ), 720P ( 1280 × 720 ), D1, VGA (640×480), 480×240, CIF                                                      |            |           |          |
| Main Stream                | 4MP(1~25fps)/3MP/1080P/720P (60Hz: 1~30fps; 50Hz: 1~25fps)                                                                                                                 |            |           |          |
| Sub Stream                 | D1/VGA/480×240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)                                                                                                                          |            |           |          |
| Bit Rate                   | 64 Kbps ~ 3 Mbps                                                                                                                                                           |            |           |          |
| Bit Rate Type              | VBR / CBR                                                                                                                                                                  |            |           |          |
| Audio Compression          | G711A/U                                                                                                                                                                    |            |           |          |
| Image Settings             | ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser                  |            |           |          |
| ROI                        | Each ROI to be configured separately                                                                                                                                       |            |           |          |
| Interfaces                 |                                                                                                                                                                            |            |           |          |
| Network                    | RJ45 (10/100 Base-T)                                                                                                                                                       |            |           |          |
| Video Output               | No                                                                                                                                                                         |            |           |          |
| Audio                      | 1CH built-in MIC                                                                                                                                                           |            |           |          |
| Storage                    | No                                                                                                                                                                         |            |           |          |
| Reset                      | No                                                                                                                                                                         |            |           |          |
| Functions                  |                                                                                                                                                                            |            |           |          |
| Remote Monitoring          | Web browser /NVR/NVMS/Mobile APP                                                                                                                                           |            |           |          |
| Web Browser                | IE 11 (plug-in required)/Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+                                                                                                |            |           |          |
| Online Connection          | Support simultaneous monitoring for up to 3 users;<br>Support multi-stream real time transmission                                                                          |            |           |          |
| Network Protocol           | TCP, UDP, IPv4, IPv6, DHCP, NTP, RTSP, 802.1x, HTTP                                                                                                                        |            |           |          |
| Interface Protocol         | ONVIF                                                                                                                                                                      |            |           |          |
| API&SDK                    | Yes                                                                                                                                                                        |            |           |          |
| Storage                    | Network remote storage                                                                                                                                                     |            |           |          |
| Motion Detection           | Support smart motion detection; filtering motion alarm triggered by other target types except humans.                                                                      |            |           |          |
| Smart Event                | (Human) region intrusion detection, (human)line crossing detection                                                                                                         |            |           |          |
| General Function           | Watermark, video mask, heartbeat                                                                                                                                           |            |           |          |
| Security                   | Video encryption, firmware encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP |            |           |          |

|                          |                                                                         |       |
|--------------------------|-------------------------------------------------------------------------|-------|
| PoE                      | Yes, IEEE802.3af                                                        | No    |
| Supplement Light Range   | IR range: 20 ~ 30 m; white light range:10 ~ 20 m                        |       |
| Ingress Protection       | IP67                                                                    |       |
| Others                   |                                                                         |       |
| Power Supply             | DC12V/PoE                                                               | DC12V |
| Power Consumption        | < 5W                                                                    | < 4W  |
| Operating Environment    | - 20 °C ~ 55 °C (-4°F~131°F); Humidity: less than 95 % (non-condensing) |       |
| Storage Environment      | - 20 °C ~ 60°C (-4°F~140°F), Humidity: less than 95 % (non-condensing)  |       |
| Dimensions ( mm )        | Φ 94.8 × 82.8                                                           |       |
| Weight ( net )           | Approx. 0.28KG                                                          |       |
| Material                 | Plastic + Metal                                                         |       |
| Installation             | Ceiling mounting; Wall mounting                                         |       |
| Certificate              | CE, FCC                                                                 |       |
| Environmental Protection | Directive EU RoHS, WEEE(2012/19/EU) , and REACH(EC1907/2006)            |       |

## DIMENSIONS



## AVAILABLE ACCESSORIES



## AVAILABLE MODEL

|                 |                        |
|-----------------|------------------------|
| Available Model | TD-9540S4L-C(D/PE/AW1) |
|                 | TD-9540S4L-C(D/AW1)    |